

Metsä CTO KMI

Datasheet updated: June 2024



We manufacture Metsä Crude Tall Oil (CTO) from the best quality Nordic wood. This renewable material, which replaces fossil-based materials and fossil fuels is produced sustainably at Metsä Fibre's bioproduct mill in Kemi, Finland.

Metsä CTO is typically used as a raw material in the production of adhesives, rubbers, paints, inks and biofuels. It is also used as a binder agent in cement and asphalt, and even in animal feed.

Typical product characteristics		
Property	Value	Method
Acid number	Typical 154 mg KOH/l	SCAN-T 11:72
Resin acid	Typical 29%	SCAN-T 14:78
Water content	Typical 0.5%	ASTM D 890-98
Soap number	Typical 0.1 mg KOH/l	PCTM 13

Certificates	
ISO 14001	Environmental management system
ISO 9001	Quality management system
PEFC COC	Chain of Custody, controlled sources License PEFC/02-33-21
FSC® COC/CW	Chain of Custody, controlled wood License FSC-C002102
ISO 50001	Energy management system
ISO 45001	Health and safety management system
ISO 22000	Food safety management system
ISCC	International Sustainability & Carbon Certification

Raw material	
Pine (pinus sylvestris)	60-70%
Spruce (picea abies)	15-25%
Birch (betula verrucosa)	15-25%

Origin of raw material	
Finland	96 %
Sweden	4 %

