

Kerto® LVL

Q-panel



<STEPREF A="att_W_DataSheetGeneralText" O="PF128435"
OT="Product" VC="DA" VO="2682944" W="Approved" />

AFGØRENDE FORDELE

OVERORDNEDE DIMENSIONER

	MINIMUM (mm)	MAKSIMUM (mm)
Tykkelse	21	75 mm
Bredde højde	200	2500 mm
Længde	2000	20000 mm

* Short lengths (< 2,000 mm) and widths under 200 mm are available on request.

** For products wider than 1,830 mm, maximum length is 20,000 mm.

STANDARD TOLERANCER

	STØRRELSE	MINIMUM	MAKSIMUM
Tykkelse	≤ 27 mm	- 1.0 mm	+ 1.0 mm
	27 < t ≤ 57 mm	- 2.0 mm	+ 2.0 mm
	t > 57 mm	- 3.0 mm	+ 3.0 mm
Bredde / højde	< 400 mm	- 2.0 mm	+ 2.0 mm
	≥ 400 mm	- 0,5 %	+ 0,5 %
Længde	Alle	- 5.0 mm	+ 5.0 mm

In moisture content of 10 ±2 %. Special tolerances are available on request.

ANDRE STØRRELSER FÅS EFTER ANMODNING

TYKKELSE (mm)	ANTAL LAG	LAY-UP
21	7	I-III-I
21	7	II-I-II
24	8	II-II-II
27	9	II-III-II
30	10	II-III-II
33	11	II-III-II
39	13	II-III-III-II
45	15	II-III-III-II
51	17	II-III-III-III-II
57	19	II-III-III-III-II
63	21	II-III-III-III-III-II
69	23	II-III-III-III-III-II
75	25	II-III-III-III-III-II

Andre størrelser fås efter anmodning

Kerto® LVL

Q-panel

<STEPTABLE O="PF128435" OT="Product" TT="107754" VC="DA"
VO="2682944" W="Approved" />

<STEPREF A="att_W_DatasheetDisclaimer" O="PF128435" OT="Product" VC="DA"
VO="2682944" W="Approved" />

04/2026

METSÄ WOOD
P.O. Box 50, 02020 Metsä, Finland
Tel. +358 1046 05
www.metsawood.com/kerto

