

# DECLARATION OF CONFORMITY

**UK  
CA**

NO. MWUK/CL/212-005/UKCA/UKDOC

---

**1. PRODUCT-TYPE:**

Preservative treated wall and ceiling solid softwood cladding

**2. INTENDED USE OR USES:**

Wall and ceiling cladding for internal and external uses

**3. MANUFACTURER:**

Metsä Wood UK Ltd, Old Golf Course, Fishtoft Road,  
Boston, Lincs. PE21 0BJ.

[www.metsawood.com](http://www.metsawood.com)

**5. SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE:**

(AVCP) System 4

**6A. DESIGNATED STANDARD:**

EN 14915:2013 + A2:2020

## 7. DECLARED PERFORMANCE

ESSENTIAL CHARACTERISTICS	PERFORMANCE	DESIGNATED TECHNICAL SPECIFICATION	
Reaction to fire	D - s2,d 0	EN14915:2013 +A2:2020	
Emission (release) of formaldehyde	E1		
Water vapour permeability	20 $\mu$ / 50 $\mu$		
Sound absorption	0,10 / 0,30 Hz		
Content of Pentachlorophenol	$\leq 5 \times 10^{-6n}$		
Thermal conductivity	0,13 W/(m K) Pine 0,12 W/(m K) Spruce		
Resistance to Fixings	NPD		
Durability against biological attack (Use Class EN 335)	Use Class 2		
Retention (EN 351-1:2007)	Wood Preservative (BS EN 599-2:1997)		EN 14915:2013 +A2:2020
	Vacsol Aqua 6112	Protim E406	
	4.8kg / m <sup>3</sup>	45kg / m <sup>3</sup>	
Penetration (EN 351-1:2007)	NP1		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with The Construction Products (Amendment etc.) (EU Exit) Regulations 2019 (S.I. 2019/465), under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Matti Pajula**  
**Managing Director, Metsä Wood UK**  
**Metsä Wood UK Ltd**

Boston, 06.12.2022

