

# DECLARATION OF CONFORMITY

**UK  
CA**

No. MWUK/FL/213-005/UKCA/UKDOC

---

**1. PRODUCT-TYPE:**

Preservative treated solid softwood tongue & groove flooring

**2. INTENDED USE OR USES:**

Preservative treated solid softwood tongue & groove flooring for internal use, to be mechanically fixed

**3. MANUFACTURER:**

Metsä Wood UK Ltd, Old Golf Course, Fishtoft Road,  
Boston, Lincs. PE21 0BJ.

[www.metsawood.com](http://www.metsawood.com)

**5. SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE:**

(AVCP) System 4

**6A. DESIGNATED STANDARD:**

EN 14342:2013

## 7. DECLARED PERFORMANCE

ESSENTIAL CHARACTERISTICS	PERFORMANCE	DESIGNATED TECHNICAL SPECIFICATION	
Reaction to fire	F fl	EN 14342:2013	
Minimum mean density	500kg / m <sup>3</sup> Pine (Pinus sylvestris) 440kg / m <sup>3</sup> Spruce (Picea abies)		
Minimum overall thickness	18-28mm		
Emission (release) of formaldehyde	E1		
Content of pentachlorophenol	< 5 ppm		
Breaking Strength	NPD		
Slipperiness USRV	NPD		
Thermal conductivity	0,13 W/(m K) Pine 0,12 W/(m K) Spruce		
Biological durability (EN 335)	Use Class 2		
Retention (EN 351-1:2007)	Wood Preservative (EN 599-2:1997)		EN 14342:2013
	Vacsol Aqua 6112	Protim E406	
	4.8kg / m <sup>3</sup>	45kg / m <sup>3</sup>	
Penetration (EN 351-1:2007)	NP1		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with The Construction Products (Amendment etc.) (EU Exit) Regulations 2019 (S.I. 2019/465), under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Matti Pajula**  
Managing Director, Metsä Wood UK  
Metsä Wood UK Ltd



Boston, 06.12.2022