

DECLARATION OF PERFORMANCE

**UK
CA**

No. MWUK/FL/213-006/UKCA/UKDOC

1. PRODUCT-TYPE:

Preservative treated solid softwood tongue & groove flooring

2. INTENDED USE OR USES:

Preservative treated solid softwood tongue & groove flooring for internal/external use, to be mechanically fixed

3. MANUFACTURER:

Metsä Wood UK Ltd, Old Golf Course, Fishtoft Road,
Boston, Lincs. PE21 0BJ.

www.metsawood.com

5. SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE:

(AVCP) System 4

6A. DESIGNATED STANDARD:

EN 14342:2013

7. DECLARED PERFORMANCE

ESSENTIAL CHARACTERISTICS		PERFORMANCE			DESIGNATED TECHNICAL SPECIFICATION
Reaction to fire		F fl			EN 14342:2013
Minimum mean density		500kg / m ³ Pine (Pinus sylvestris) 440kg / m ³ Spruce (Picea abies)			
Minimum overall thickness		18-28mm			
Emission (release) of formaldehyde		E1			
Content of pentachlorophenol		< 5 ppm			
Breaking Strength		NPD			
Slipperiness USRV		NPD			
Thermal conductivity		0,13 W/(m K) Pine 0,12 W/(m K) Spruce			
Biological durability (EN 335)		Use Class 3			
Retention (EN 351-1:2007)		Wood Preservative (EN 599-2:1997)			EN 14342:2013
		Tanalith E 8000	Wolmanit CX-8WB	Celcure AC500	
		8.5 kg/m ³	7.5 kg/m ³	10.5 kg/m ³	
Penetration (EN 351-1:2007)	Pine	NP5			
	Spruce	NP2			

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with The Construction Products (Amendment etc.) (EU Exit) Regulations 2019 (S.I. 2019/465), under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Matti Pajula
Managing Director, Metsä Wood UK
Metsä Wood UK Ltd



Boston, 06.12.2022