

DECLARATION OF PERFORMANCE

NO. MWUK/CL/212-006/CPR/DOP



1. PRODUCT-TYPE:

Preservative treated wall and ceiling solid softwood cladding

2. INTENDED USE OR USES:

Wall and ceiling cladding for internal and external uses

3. MANUFACTURER:

Metsä Wood UK Ltd, Old Golf Course, Fishtoft Road,
Boston, Lincs. PE21 0BJ.

www.metsawood.com

Please visit www.metsawood.com/dop for DoPs online

5. SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE:

(AVCP) System 4

6A. HARMONISED STANDARD:

EN 14915:2013+A1:2017

7. DECLARED PERFORMANCE

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	D - s2,d 0	EN 14915:2013+A1:2017
Emission (release) of formaldehyde	E1	
Water vapour permeability	20 μ / 50 μ	
Sound absorption	0,10 / 0,30 Hz	
Content of Pentachlorophenol	$\leq 5 \times 10^{-6n}$	
Thermal conductivity	0,13 W/(m K) Pine 0,12 W/(m K) Spruce	
Resistance to Fixings	NPD	
Durability against biological attack (Use Class EN 335)	Use Class 3	

Wood Preservative (EN 599-2:1997)	Retention (EN 351-1:2007)	Penetration (EN 351-1:2007)		HARMONISED TECHNICAL SPECIFICATION
		Pine	Spruce	
Tanalith E 8000	8.5kg / m ³	NP5	NP2	EN 14915:2013+A1:2017
Wolmanit CX-8WB	7.5kg / m ³			
Celcure AC500	10.5kg / m ³			

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Matti Pajula
Managing Director, Metsä Wood UK
Metsä Wood UK Ltd



Boston, 21.07.2020

.....